



## Safety Data Sheet



### 1 - Identification

<b>Trade Name:</b> 3-In-One® Professional Silicone Spray Lubricant	<b>Canadian Office:</b> WD-40 Products [Canada] Ltd. P.O. Box 220 Toronto, Ontario M9C 4V3 <b>Information Phone #:</b> (416) 622-9881 <b>Emergency Phone # 24 hr:</b> Canutec: (613) 996-6666 - Designated for use only in the event of chemical emergencies involving a spill, leak, fire exposure or accident involving chemicals
<b>Product Use:</b> Cleaner, Lubricant	
<b>Restrictions on Use:</b> None identified	
<b>SDS Date Of Preparation:</b> September 19, 2016	

### 2 – Hazards Identification

**WHMIS 2015/GHS Classification:**

Flammable Aerosol Category 1

Gas Under Pressure: Compressed Gas

Aspiration Toxicity Category 1

Skin Sensitizer Category 1

Specific Target Organ Toxicity Single Exposure Category 3 (nervous system effects)

Note: This product is a consumer product and is labeled in accordance with the Consumer Chemicals and Containers Regulations (CCCR) which take precedence over WHMIS 2015 labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

**Label Elements:****DANGER!**

Extremely Flammable Aerosol.

Contains gas under pressure; may explode if heated.

May be fatal if swallowed and enters airways.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

**Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Avoid breathing vapors or mist.

Contaminated work clothing should not be allowed out of the workplace.

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

**Response**

IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.

**Storage**

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.

**Disposal**

Dispose of contents and container in accordance with local and national regulations.

**3 - Composition/Information on Ingredients**

Ingredient	CAS #	Weight Percent	WHMIS 2015/ GHS Classification
LVP Aliphatic Hydrocarbon	64742-47-8	35-45%	Aspiration Toxicity Category 1
Propellant (propane, n-butane, Isobutane)	68476-86-8	35-45%	Flammable Gas Category 1 Gas Under Pressure, Compressed Gas
Aliphatic Hydrocarbon	64742-47-8	10-20%	Flammable Liquid Category 3 Aspiration Toxicity Category 1 Specific Target Organ Toxicity Single Exposure Category 3 (nervous system effects)
Poly(dimethylsiloxane)	63148-62-9	1-5%	Not Hazardous
Fragrance	Mixture	<1%	Skin Sensitizer Category 1

**4 – First Aid Measures**

**Ingestion (Swallowed):** Aspiration Hazard. DO NOT induce vomiting. Call physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately.

**Eye Contact:** Flush thoroughly with water. Remove contact lenses if present after the first 5 minutes and continue flushing for several more minutes. Get medical attention if irritation persists.

**Skin Contact:** Wash with soap and water. If irritation or rash occurs, get medical attention.

**Inhalation (Breathing):** If irritation is experienced, move to fresh air. Get medical attention if irritation or other symptoms develop and persist.

**Signs and Symptoms of Exposure:** Harmful or fatal is swallowed. Aspiration of liquid into the lungs during swallowing or vomiting may cause lung damage. May cause eye and respiratory irritation. May cause skin sensitization. Skin contact may cause drying of the skin. Inhalation of mists or vapors may cause drowsiness, dizziness and other nervous system effects.

**Indication of Immediate Medical Attention/Special Treatment Needed:** Immediate medical attention is needed for ingestion.

**5 – Fire Fighting Measures**

**Suitable (and unsuitable) Extinguishing Media:** Use water fog, dry chemical, carbon dioxide or foam. Do not use water jet or flooding amounts of water. Burning product will float on the surface and spread fire.

**Specific Hazards Arising from the Chemical:** Extremely Flammable aerosol. Contents under pressure. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. A vapor and air mixture can create an explosion hazard in confined spaces. Combustion will produce oxides of carbon and hydrocarbons.

**Special Protective Equipment and Precautions for Fire-Fighters:** Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting containers.

**6 – Accidental Release Measures**

**Personal Precautions, Protective Equipment and Emergency Procedures:** Wear appropriate protective clothing (see Section 8). Eliminate all sources of ignition and ventilate area.

**Methods and Materials for Containment/Cleanup:** Leaking cans should be placed in a plastic bag or open pail until the pressure has dissipated. Contain and collect liquid with an inert absorbent and place in a container for disposal. Clean spill area thoroughly. Report spills to authorities as required.

## 7 – Handling and Storage

**Precautions for Safe Handling:** Avoid contact with eyes. Avoid prolonged contact with skin. Avoid breathing vapors or aerosols. Use only with adequate ventilation. Keep away from heat, sparks, pilot lights, hot surfaces and open flames. Unplug electrical tools, motors and appliances before spraying or bringing the can near any source of electricity. Electricity can burn a hole in the can and cause contents to burst into flames. To avoid serious burn injury, do not let the can touch battery terminals, electrical connections on motors or appliances or any other source of electricity. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children. Do not puncture, crush or incinerate containers, even when empty.

**Conditions for Safe Storage:** Store in a cool, well-ventilated area, away from incompatible materials. Do not store above 120°F or in direct sunlight. U.F.C (NFPA 30B) Level 3 Aerosol. Store away from oxidizers.

## 8 – Exposure Controls/Personal Protection

Chemical	Occupational Exposure limits
LVP Aliphatic Hydrocarbon	1200 mg/m <sup>3</sup> TWA (manufacturer recommended)
Propane	1000 ppm TWA Canada-Ontario (as Aliphatic Hydrocarbon gases [C1-C4]) 1000 ppm TWA Canada- Québec 1000 ppm TWA British Columbia (as Aliphatic Hydrocarbon gases [C1-C4])
n-Butane	1000 ppm STEL ACGIH TLV 800 ppm TWA Canada- Québec 800 ppm TWA Canada- Ontario (as Aliphatic Hydrocarbon gases [C1-C4]) 600 ppm TWA, 750 ppm STEL British Columbia
Isobutane	1000 ppm STEL ACGIH TLV (as Butane, all isomers) 800 ppm TWA Canada- Ontario (as Aliphatic Hydrocarbon gases [C1-C4])
Aliphatic Hydrocarbon	1200 mg/m <sup>3</sup> TWA (manufacturer recommended)
Poly(dimethylsiloxane)	None Established
Fragrance	None Established

### The Following Controls are Recommended for Normal Consumer Use of this Product

**Appropriate Engineering Controls:** Use in a well-ventilated area.

**Personal Protection:**

**Eye Protection:** Avoid eye contact. Always spray away from your face.

**Skin Protection:** Avoid prolonged or repeated skin contact. Chemical resistant gloves recommended for operations where skin contact is likely.

**Respiratory Protection:** None needed for normal use with adequate ventilation.

### For Bulk Processing or Workplace Use the Following Controls are Recommended

**Appropriate Engineering Controls:** Use adequate general and local exhaust ventilation to maintain exposure levels below that occupational exposure limits.

**Personal Protection:**

**Eye Protection:** Safety glasses with side shields are recommended where eye contact is possible.

**Skin Protection:** Wear appropriate protective clothing and chemical-resistant gloves to avoid prolonged or repeated skin contact. Wash thoroughly after handling.

**Respiratory Protection:** None required if ventilation is adequate. If the occupational exposure limits are exceeded, wear a NIOSH approved respirator. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

**Work/Hygiene Practices:** Avoid contact with the eyes and skin. Wash hands thoroughly after use.

## 9 – Physical and Chemical Properties

Appearance:	Colorless liquid	Flammable Limits: (Solvent Portion)	LEL: 0.6% UEL: 5.6%
Odor:	Mild petroleum odor	Vapor Pressure:	Not Determined
Odor Threshold:	Not established	Vapor Density:	Not Determined
pH:	Not Applicable	Relative Density:	Not Determined
Melting/Freezing Point:	Not established	Solubilities:	Insoluble in water

Boiling Point/Range:	148.89-212.78°C (300-415°F) (Solvent)	Partition Coefficient; n-octanol/water:	Not established
Flash Point:	40-43°C (-109°F) (Solvent)	Autoignition Temperature:	Not established
Evaporation Rate:	Not established	Decomposition Temperature:	Not established
Flammability (solid, gas):	Flammable Aerosol	Viscosity:	Not established
VOC:	58.11%	Pour Point:	Not established

## 10 – Stability and Reactivity

**Reactivity:** Not reactive under normal conditions

**Chemical Stability:** Stable

**Possibility of Hazardous Reactions:** May react with strong oxidizers generating heat.

**Conditions to Avoid:** Avoid heat, sparks, flames and other sources of ignition. Do not puncture or incinerate containers.

**Incompatible Materials:** Strong acids, alkalis, and oxidizers.

**Hazardous Decomposition Products:** Carbon monoxide, carbon dioxide, and/or unburned hydrocarbons.

## 11 – Toxicological Information

**Symptoms of Overexposure:**

**Inhalation:** High concentrations may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea. Intentional abuse may be harmful or fatal.

**Skin Contact:** Prolonged and/or repeated contact may produce mild irritation and defatting with possible dermatitis. May cause allergic skin reaction (sensitization).

**Eye Contact:** Contact may be irritating to eyes. May cause redness, stinging, swelling and tearing.

**Ingestion:** This product has low oral toxicity. If swallowed, this material may cause irritation of the mouth, throat and esophagus. Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea, dizziness, drowsiness and other central nervous system effects. This product is an aspiration hazard. If swallowed, can enter the lungs and may cause chemical pneumonitis, severe lung damage and death.

**Chronic Effects:** None expected.

**Carcinogen Status:** None of the components are listed as a carcinogen or suspect carcinogen by IARC, NTP, ACGIH or OSHA.

**Reproductive Toxicity:** None of the components is considered a reproductive hazard.

**Numerical Measures of Toxicity:**

The oral toxicity of this product is estimated to be greater than 5,000 mg/kg and the dermal toxicity greater than 2,000 mg/kg based on an assessment of the ingredients. This product is not classified as toxic by established criteria. It is an aspiration hazard.

## 12 – Ecological Information

**Ecotoxicity:** No specific aquatic toxicity data is currently available; however components of this product are expected to be harmful to aquatic organisms

**Persistence and Degradability:** No data available.

**Bioaccumulative Potential:** No data available

**Mobility in Soil:** No data available

**Other Adverse Effects:** None known

## 13 - Disposal Considerations

Aerosol containers should not be punctured, compacted in home trash compactors or incinerated. Empty containers may be disposed of through normal waste management options. Dispose of all waste product, absorbents, and other materials in accordance with applicable Federal, state and local regulations.

## 14 – Transportation Information

DOT Surface Shipping Description: UN1950, Aerosols, 2.1 Ltd. Qty

(Note: Shipping Papers are not required for Limited Quantities unless transported by air or vessel – each package must be marked with the Limited Quantity Mark)

Canadian TDG Classification: Limited Quantity

IMDG Shipping Description: Un1950, Aerosols, 2.1, LTD QTY

ICAO Shipping Description: UN1950, Aerosols, flammable, 2.1

NOTE: WD-40 Company does not test aerosol cans to assure that they meet the pressure and other requirements for transport by air. We do not recommend that our aerosol products be transported by air.

### 15 – Regulatory Information

**National Pollutant Release Inventory (NPRI):** This product contains the following chemicals that are listed on the NPRI Substance List: LVP Aliphatic Hydrocarbon (64742-47-8) 35-45%, Aliphatic Hydrocarbon (64742-47-8) 10-20%, Propellant (propane, n-butane, isobutane) 35-45%

**Canadian Environmental Protection Act:** All of the ingredients are listed on the Canadian Domestic Substances List or exempt from notification.

### 16 – Other Information

**HMIS Hazard Rating:**

**Health – 2 (moderate hazard), Fire Hazard – 4 (severe hazard), Physical Hazard – 0 (minimal hazard)**

Revision Date: September 19, 2016

Supersedes: February 3, 2014

Prepared by: Industrial Health & Safety Consultants, Inc. Shelton, CT, USA

Reviewed by: I. Kowalski

Regulatory Affairs Department

1009100/No.0069403