

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product identifier	LPS® 2 (Aerosol)	
Version #	02	
Issue date	09-22-2014	
Revision date	10-25-2014	
Supersedes date	09-22-2014	
CAS #	Mixture	
Part Number	C30216	
Product use	An industrial lubricant designed to displace moisture from equipment, provide heavy-duty lubrication and rust prevention.	
Manufacturer information	LPS Laboratories, a division of Illinois Tool Works, Inc. 4647 Hugh Howell Rd Tucker, Georgia 30084 United States www.lpslabs.com 1-800-241-8334/ 770-243-8800 Chemtrec 1-800-424-9300	
Supplier	Not available.	
2. Hazards Identification		
Emergency overview	DANGER	
	CONTENTS UNDER PRESSURE. Flammable aerosol. Pressurized container may explode when exposed to heat or flame.	
	Irritating to eyes and skin. Vapors may cause drowsiness and dizziness.	
Potential health effects		
Routes of exposure	Eye contact. Skin contact. Inhalation. Ingestion.	
Eyes	Contact with eyes may cause irritation. Avoid contact with eyes.	
Skin	May cause skin irritation. Avoid contact with the skin.	
Inhalation	Avoid breathing dust/fume/gas/mist/vapors/spray. Prolonged inhalation may be harmful. May cause irritation of respiratory tract.	
Ingestion	Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Harmful: may cause lung damage if swallowed. Do not ingest.	
Target organs	Eyes. Skin. Central nervous system. Respiratory system.	
Signs and symptoms	Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. Drowsiness and dizziness. Narcosis. Decrease in motor functions. Behavioral changes.	
Potential environmental effects	Ecological injuries are not known or expected under normal use.	

3. Composition / Information on Ingredients

Hazardous components	CAS #	Percent
CARBON DIOXIDE	124-38-9	1 - 5
Non-hazardous components	CAS #	Percent
Distillates Petroleum, Hydroteated Light	64742-47-8	70 - 80
Petroleum Oil	64742-52-5	10 - 20

4. First Aid Measures

First aid procedures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. For breathing difficulties, oxygen may be necessary. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Notes to physician	Provide general supportive measures and treat symptomatically.
General advice	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Call a POISON CENTER or doctor/physician if you feel unwell.

5. Fire Fighting Measures

Flammable properties	Flammable by WHMIS criteria. Heat may cause the containers to explode. Ruptured cylinders may rocket.
Extinguishing media	
Suitable extinguishing media	Powder. Alcohol resistant foam. Water. Water spray. Dry chemicals. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Protection of firefighters	
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. Fire may produce irritating, corrosive and/or toxic gases.
Protective equipment for firefighters	Firefighters should wear full protective clothing including self contained breathing apparatus.
Fire fighting equipment/instructions	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Cool containers exposed to flames with water until well after the fire is out.
Explosion data	
Sensitivity to static discharge	Yes
Sensitivity to mechanical impact	None known.
Hazardous combustion products	May include oxides of carbon.

6. Accidental Release Measures

Personal precautions	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the MSDS.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not contaminate water.
Methods for containment	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Use water spray to reduce vapors or divert vapor cloud drift. Keep out of low areas. Prevent entry into waterways, sewer, basements or confined areas.
Methods for cleaning up	Should not be released into the environment. Stop the flow of material, if this is without risk. Isolate area until gas has dispersed. Following product recovery, flush area with water. Clean up in accordance with all applicable regulations. For waste disposal, see section 13 of the MSDS.
Other information	Clean up in accordance with all applicable regulations.

7. Handling and Storage

Handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Do not get this material on clothing. Do not use in areas without adequate ventilation. Wear positive pressure self-contained breathing apparatus (SCBA). Wear personal protective equipment. Wash thoroughly after handling. Avoid release to the environment.
Storage	Contents under pressure. The pressure in sealed containers can increase under the influence of heat. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a closed container away from incompatible materials. Store in a well-ventilated place. Keep container dry. Store away from incompatible materials (see Section 10 of the MSDS). Keep out of the reach of children.

8. Exposure Controls / Personal Protection

ACGIH Components	Туре	Value	Form
Petroleum Oil (CAS 64742-52-5)	TWA	5 mg/m3	Oil mist
US. ACGIH Threshold Limit Value			
Components	Туре	Value	
CARBON DIOXIDE (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
Canada. Alberta OELs (Occupatio	nal Health & Safety Code, Scl	hedule 1, Table 2)	
Components	Туре	Value	
CARBON DIOXIDE (CAS 124-38-9)	STEL	54000 mg/m3	
,		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
CARBON DIOXIDE (CAS 124-38-9)	STEL	15000 ppm	
124-38-9)	STEE	15000 ppm	
/			
,	TWA	5000 ppm	
Canada. Manitoba OELs (Reg. 217	7/2006, The Workplace Safety	And Health Act)	
Canada. Manitoba OELs (Reg. 217 Components	7/2006, The Workplace Safety Type	And Health Act) Value	
Canada. Manitoba OELs (Reg. 217 Components CARBON DIOXIDE (CAS	7/2006, The Workplace Safety Type STEL	And Health Act) Value 30000 ppm	
Canada. Manitoba OELs (Reg. 217 Components CARBON DIOXIDE (CAS 124-38-9)	7/2006, The Workplace Safety Type STEL TWA	And Health Act) Value 30000 ppm 5000 ppm	
Canada. Manitoba OELs (Reg. 217 Components CARBON DIOXIDE (CAS 124-38-9) Canada. Ontario OELs. (Control o	7/2006, The Workplace Safety Type STEL TWA f Exposure to Biological or C	And Health Act) Value 30000 ppm 5000 ppm hemical Agents)	
Canada. Manitoba OELs (Reg. 217 Components CARBON DIOXIDE (CAS 124-38-9) Canada. Ontario OELs. (Control o	7/2006, The Workplace Safety Type STEL TWA	And Health Act) Value 30000 ppm 5000 ppm	
Canada. Manitoba OELs (Reg. 217 Components CARBON DIOXIDE (CAS 124-38-9) Canada. Ontario OELs. (Control o Components CARBON DIOXIDE (CAS 124-38-9)	7/2006, The Workplace Safety Type STEL TWA f Exposure to Biological or C	And Health Act) Value 30000 ppm 5000 ppm hemical Agents)	
Canada. Manitoba OELs (Reg. 217 Components CARBON DIOXIDE (CAS 124-38-9) Canada. Ontario OELs. (Control o Components CARBON DIOXIDE (CAS	7/2006, The Workplace Safety Type STEL TWA f Exposure to Biological or C Type	And Health Act) Value 30000 ppm 5000 ppm hemical Agents) Value	
Canada. Manitoba OELs (Reg. 217 Components CARBON DIOXIDE (CAS 124-38-9) Canada. Ontario OELs. (Control o Components CARBON DIOXIDE (CAS 124-38-9) Canada. Quebec OELs. (Ministry o	7/2006, The Workplace Safety Type STEL TWA f Exposure to Biological or C Type STEL TWA	And Health Act) Value 30000 ppm 5000 ppm hemical Agents) Value 30000 ppm 5000 ppm	Environment)
Canada. Manitoba OELs (Reg. 217 Components CARBON DIOXIDE (CAS 124-38-9) Canada. Ontario OELs. (Control o Components CARBON DIOXIDE (CAS 124-38-9) Canada. Quebec OELs. (Ministry o Components CARBON DIOXIDE (CAS	7/2006, The Workplace Safety Type STEL TWA f Exposure to Biological or C Type STEL TWA of Labor - Regulation Respect	And Health Act) Value 30000 ppm 5000 ppm hemical Agents) Value 30000 ppm 5000 ppm	Environment)
Canada. Manitoba OELs (Reg. 217 Components CARBON DIOXIDE (CAS 124-38-9) Canada. Ontario OELs. (Control o Components CARBON DIOXIDE (CAS 124-38-9) Canada. Quebec OELs. (Ministry o Components	7/2006, The Workplace Safety Type STEL TWA f Exposure to Biological or C Type STEL TWA of Labor - Regulation Respect Type	And Health Act) Value 30000 ppm 5000 ppm hemical Agents) Value 30000 ppm 5000 ppm ting the Quality of the Work E Value	Environment)

Canada. Quebec OELs. (Min Components	Туре	Value	
	TWA	9000 mg/m3 5000 ppm	
U.S OSHA Components	Туре	Value	Form
Petroleum Oil (CAS	PEL	5 mg/m3	Oil mist
64742-52-5) US. OSHA Table Z-1 Limits f Components	for Air Contaminants (29 CFR 1910.1000) Type	Value	
CARBON DIOXIDE (CAS 124-38-9)	PEL	9000 mg/m3	
ological limit values	No biological exposure limits noted for the ingr	5000 ppm redient(s).	
gineering controls	Ensure adequate ventilation, especially in con-	fined areas.	
rsonal protective equipment Eye/face protection	Wear safety glasses with side shields (or gogg	gles).	
Skin protection	Wear suitable protective clothing.		
Respiratory protection	In case of insufficient ventilation, wear suitable	e respiratory equipmer	nt.
Hand protection	Chemical resistant gloves are recommended.		
Physical & Chemical Pro	operties		
pearance	Liquid.		
Physical state	Gas.		
Form	Aerosol.		
Color	Brown		
or	Slight petroleum odor, Cherry		
or threshold	Not established		
	Not applicable		
por pressure	< 0.05 mm Hg @ 20ºC (dispensed liquid)		
por density	4.7 (air = 1)		
iling point	383 °F (195 °C) @ 101 kPa		
Iting point/Freezing point	< -58 °F (< -50 °C)		
lubility (water)	< 3 %		
ecific gravity	0.82 - 0.86 @ 20°C		
lative density	Not available.		
sh point	174.2 °F (79.0 °C) Tag Closed Cup (dispensed	l liquid)	
mmability limits in air, per, % by volume	7 %		
mmability limits in air, /er, % by volume	0.6 %		
to-ignition temperature	> 442.4 °F (> 228 °C)		
aporation rate	< 0.1 BuAc		
cosity	< 7 cSt		
cosity temperature	77 °F (25 °C)		
rcent volatile	92 - 95 %		
rtition coefficient octanol/water)	< 1		
ner data Decomposition	Not established		
temperature			

Heat of combustion > 30 kJ/g

10. Chemical Stability & Reactivity Information

Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.
Possibility of hazardous reactions	Hazardous polymerization does not occur.

11. Toxicological Information

Toxicological data

l'oxicological data			
Components	Species Test Results		
Petroleum Oil (CAS 64742-52-5)			
Acute			
Dermal			
LD50	Rabbit	> 2000 mg/kg	
		> 2000 mg/kg, 24 Hours	
Inhalation			
LC50	Rat	2.18 mg/l, 4 Hours	
Oral			
LD50	Rat	5000 mg/kg	
Acute effects	Narcotic effects.		
Sensitization	Based on available data, the classi	fication criteria are not met.	
Local effects	Irritating to eyes and skin. Irritating irritation, nausea, vomiting and diar	to respiratory system. Ingestion may cause gastrointestinal rhea.	
Chronic effects	Prolonged inhalation may be harmf	ul.	
Carcinogenicity	This product is not considered to be	e a carcinogen by IARC, ACGIH, NTP, or OSHA.	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/irritation	Causes serious eye irritation.		
Mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Reproductive effects	This product is not expected to cau	se reproductive or developmental effects.	
Teratogenicity	Not available.		
Symptoms and target organs	swelling, and blurred vision. Exposu	res, respiratory system and skin. Symptoms may include stinging, tearing, redness blurred vision. Exposure may cause temporary irritation, redness, or discomfort. a narcotic effect and may cause headache, fatigue, dizziness and nausea.	
Synergistic materials	Not available.		
12. Ecological Information	ı		
Ecotoxicological data	No ecotoxicity data noted for the ingredient(s).		
Ecotoxicity		rironmentally hazardous. However, this does not exclude the lls can have a harmful or damaging effect on the environment.	
Environmental effects	An environmental hazard cannot be	e excluded in the event of unprofessional handling or disposal.	
Aquatic toxicity		rironmentally hazardous. However, this does not exclude the lls can have a harmful or damaging effect on the environment.	
Persistence and degradability	Not inherently biodegradable.		
Partition coefficient LPS® 2 (Aerosol)	<	1	
Other adverse effects	None known.		

13. Disposal Considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Dispose in accordance with all applicable regulations.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport Information

TD	G	
	UN number	UN1950
	UN proper shipping name	Aerosols, flammable
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Packing group	Not applicable.
	Environmental hazards	No
	Special precautions for user	Not available.
ΙΑΤ	A	
	UN number	UN1950
	UN proper shipping name	Aerosols, flammable
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not applicable.
	Environmental hazards	No.
	ERG Code	10L
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, MSDS and emergency procedures before handling.
	Other information	
	Passenger and cargo aircraft	Allowed.
	Cargo aircraft only	Allowed.
IMI	DG J	
	UN number	UN1950
	UN proper shipping name	AEROSOLS, flammable
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not applicable.
	Environmental hazards	
	Marine pollutant	No
	EmS	Not available.
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, MSDS and emergency procedures before handling.
ΙΛΤ		

IATA; IMDG; TDG



15. Regulatory Information

Canadian regulations


This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

Controlled

WHMIS status WHMIS classification

International Inventories

A - Compressed Gas **B5 - Flammable Aerosols** D2B - Other Toxic Effects-TOXIC



Country(s) or region Inventory name On inventory (yes/no)* Australia Australian Inventory of Chemical Substances (AICS) Yes Domestic Substances List (DSL) Canada Yes Canada Non-Domestic Substances List (NDSL) No China Inventory of Existing Chemical Substances in China (IECSC) No Europe European Inventory of Existing Commercial Chemical Yes Substances (EINECS) Europe European List of Notified Chemical Substances (ELINCS) No Inventory of Existing and New Chemical Substances (ENCS) Japan No Korea Existing Chemicals List (ECL) Yes New Zealand Inventory New Zealand No Philippines Philippine Inventory of Chemicals and Chemical Substances Yes (PICCS) United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Prepared by	Not available.
This data sheet contains changes from the previous version in section(s):	Product and Company Identification: Alternate Trade Names