

# SAFETY DATA SHEET

# 1. Identification

Product identifier	LPS® 3 (Aerosol)		
Other means of identification			
Part Number	C30316		
Recommended use	A specialized soft-film spray coating designed to prevent rust and corrosion on steel, aluminum and other metals.		
<b>Recommended restrictions</b>	None known.		
Manufacturer/Importer/Supplier/	Distributor information		
Manufacturer			
Manufacturer			
Company name	ITW Pro Brands		
Address	4647 Hugh Howell Rd.		
	Tucker, GA 30084		
Country	(U.S.A.)		
	Tel: +1 770-243-8800		
In Case of Emergency	1-800-424-9300		
	1-703-527-3887		
Website	www.lpslabs.com		
E-mail	lpssds@itwprobrands.com		
Supplier	ITW Permatex Canada		
	1-35 Brownridge Road		
	Halton Hills, ON, L7G 0C6 Canada		
	1-800-241-8334		
2. Hazard(s) identification			
Physical hazards	Flammable aerosols	Category 1	
-	Gases under pressure	Compressed gas	
Health hazards	Skin corrosion/irritation	Category 2	
	Serious eye damage/eye irritation	Category 2A	
	Specific target organ toxicity, single exposure		
Environmental hazards	Not classified.		
Label elements			
Laber elements			
Signal word	Danger		
Hazard statement	-	nder pressure; may explode if heated. Causes skin	
	irritation. Causes serious eye irritation. May ca		
Precautionary statement			
Prevention		surfaces No smoking. Do not spray on an open	
		r burn, even after use. Avoid breathing gas. Use sh thoroughly after handling. Wear protective gloves	
	and eye/face protection.	sh thoroughly after handling. Wear protective gloves	
Response	If swallowed: Call a poison center/doctor if you	a feel unwell. Rinse mouth. If inhaled: Remove	
	person to fresh air and keep comfortable for b	reathing. Call a POISON CENTER or	
		Rinse cautiously with water for several minutes.	
		o do. Continue rinsing. If eye irritation persists: Get plenty of water. Take off contaminated clothing	
	and wash it before reuse. If skin irritation occu		
Material name: LPS® 3 (Aerosol)		SDS CANADA	

Storage	Keep container tightly closed. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazards	None known.
Supplemental information	None known.

# 3. Composition/information on ingredients

### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Distillates Petroleum Hydrotreated Light		64742-47-8	50 - 60
1-butoxy-2-propanol		5131-66-8	1 - 10
Acetone		67-64-1	1 - 10
Distillates Petroleum Hydrotreated Heavy		64742-54-7	1 - 10
Carbon Dioxide		124-38-9	1 - 5
Calcium Carbonate		471-34-1	0.1 - 1
Hydrodesulferized Heavy Petroleum Naptha	1	64742-82-1	0.1 - 1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin. Rash. Symptoms of overexposure can include shortness of breath, drowsiness, headaches, confusion, decreased coordination, visual disturbances and vomiting, and are reversible if exposure is stopped.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim under observation. Symptoms may be delayed.
General information	In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Powder. Alcohol resistant foam. Water. Water spray. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed. Fire may produce irritating, corrosive and/or toxic gases.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Water runoff can cause environmental damage.

Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Use water spray to cool unopened containers. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
General fire hazards	Extremely flammable aerosol.
6. Accidental release mea	sures
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. The product is immiscible with water and will spread on the water surface. Stop leak if you can do so without risk. Isolate area until gas has dispersed. Collect spillage. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling Conditions for safe storage,	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Avoid breathing gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Wash hands thoroughly after handling. Avoid release to the environment. Level 3 Aerosol.
including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. The pressure in sealed containers can increase under the influence of heat. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store locked up. Use appropriate container to avoid environmental contamination. Keep container tightly closed. Store in a well-ventilated place. Keep container dry. Keep away from food, drink and animal feedingstuffs. Keep out of the reach of children. Keep in an area equipped with sprinklers. Use care in handling/storage.

# 8. Exposure controls/personal protection

# Occupational exposure limits

ACGIH Components	Туре	Value	Form	
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	TWA	5 mg/m3	Oil mist	
US. ACGIH Threshold Limit Valu		Malara		
Components	Туре	Value		
Acetone (CAS 67-64-1)	STEL	500 ppm		
· · · ·	TWA	250 ppm		
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm		
	TWA	5000 ppm		
Canada. Alberta OELs (Occupati	onal Health & Safety Code. Sc	hedule 1. Table 2)		
Components	Туре	Value		
Acetone (CAS 67-64-1)	STEL	1800 mg/m3		
· · · /		750 ppm		
	TWA	1200 mg/m3		
		0		

Components		уре		Value	
				500 ppm	
Calcium Carbonate (CAS 471-34-1)	T١	WA		10 mg/m3	
Carbon Dioxide (CAS 124-38-9)	S	TEL	4	54000 mg/m3	
			:	30000 ppm	
	T	WA	1	9000 mg/m3	
				5000 ppm	
Canada. British Columbi		nal Exposure Limit	s for Chemical	Substances, O	ccupational Health and
Safety Regulation 296/97	-			Value	Form
Components		уре		Value	FOIII
Acetone (CAS 67-64-1)		TEL		500 ppm	
Carbon Diavida (CAC		WA		250 ppm	
Carbon Dioxide (CAS 124-38-9)	5	TEL		15000 ppm	
,	T١	WA	:	5000 ppm	
Distillates Petroleum	T	WA	:	200 mg/m3	Non-aerosol.
Hydrotreated Light (CAS 64742-47-8)					
,	(Pag 217/2006 Tha	Workplace Sefety	And Health Ast	A	
Canada. Manitoba OELs Components		ype		) Value	
Acetone (CAS 67-64-1)		TEL		500 ppm	
Acelone (CAS 67-64-1)		WA		500 ppm 250 ppm	
Carbon Dioxide (CAS		TEL		30000 ppm	
124-38-9)	U			occo ppm	
	T١	WA	:	5000 ppm	
Canada. Ontario OELs. (	-	-	-		
Components	Ту	уре	,	Value	
Acetone (CAS 67-64-1)	-	TEL		750 ppm	
		WA		500 ppm	
Carbon Dioxide (CAS 124-38-9)	S	TEL	:	30000 ppm	
124-30-3)	T١	WA	:	5000 ppm	
Canada. Quebec OELs. (	Ministry of Labor - R	Regulation Respect			vironment)
Components	-	ype		Value	Form
Acetone (CAS 67-64-1)	S	TEL		2380 mg/m3	
				1000 ppm	
	T١	WA		1190 mg/m3	
	_			500 ppm	
Calcium Carbonate (CAS 471-34-1)	T	WA		10 mg/m3	Total dust.
Carbon Dioxide (CAS 124-38-9)	S	TEL	:	54000 mg/m3	
			:	30000 ppm	
	T١	WA		9000 mg/m3	
			4	5000 ppm	
ogical limit values					
ACGIH Biological Expos	ure Indices				
Components	Value	Determinant	Specimen	Sampling 1	Гime
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*	
* - For sampling details, pl	ease see the source of	document.			
osure guidelines					
osure guidennes					

Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas.
Individual protection measures,	such as personal protective equipment
Eye/face protection	Wear safety glasses with side shields (or goggles). Eye wash fountain is recommended.
Skin protection	
Hand protection	Chemical resistant gloves are recommended.
Other	Avoid contact with clothing. Wear suitable protective clothing. Chemical resistant gloves.
Respiratory protection	No personal respiratory protective equipment normally required. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.
Thermal hazards	Not applicable.
General hygiene considerations	When using do not smoke. When using, do not eat, drink or smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

or r nyoroar ana orionnoar p	
Appearance	Cloudy. Liquid.
Physical state	Gas.
Form	Aerosol.
Color	Brown.
Odor	Mild. Cherry.
Odor threshold	Not available.
рН	Not applicable
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	64.4 °F (18.0 °C) Tag Closed Cup
Evaporation rate	151 (Ethyl Ether)
Flammability (solid, gas)	Flammable gas.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	0.6 %
Flammability limit - upper (%)	6 %
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	446 °F (230 °C)
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	7.28 lb/gal
Percent volatile	63 - 82 %

Specific gravity	0.87
VOC	62.8 % per U.S. State and Federal Consumer Product Regulations

# 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Aerosol containers are unstable at temperatures above 50°C. Avoid temperatures exceeding the flash point.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Upon decomposition this product emits acrid dense smoke with carbon dioxide, carbon monoxide, water and other products of combustion.

# 11. Toxicological information

# Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Symptoms related to the physical, chemical and toxicological characteristics	Irritating to eyes, respiratory system and skin. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

#### Information on toxicological effects

Acute t	oxicity
---------	---------

Components	Species	Test Results
1-butoxy-2-propanol (CAS	5131-66-8)	
Acute		
Dermal		
LD50	Rabbit	1400 mg/kg, 24 Hours
Oral		
LD50	Rat	> 2000 mg/kg
Calcium Carbonate (CAS	471-34-1)	
<u>Acute</u>		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours
Oral		
LD50	Rat	> 2000 mg/kg
Distillates Petroleum Hydro	otreated Heavy (CAS 64742-54-7)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 3.9 mg/l, 4 Hours
Oral		
LD50	Rat	> 2000 mg/kg
Distillates Petroleum Hydro	otreated Light (CAS 64742-47-8)	
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg

Components	Species			Test Results
Inhalation				
Vapor				
LC50	Rat			> 4.5 mg/l, 4 Hours
ydrodesulferized Heavy Petroleu	um Naptha (C	AS 64742-82-1)		
Acute				
Dermal				
LD50	Rabbit			> 1900 mg/kg, 24 Hours
Oral	_			
LD50	Rat			4820 mg/kg
Skin corrosion/irritation	Causes sk	in irritation.		
Serious eye damage/eye rritation	Causes se	rious eye irritation.		
espiratory or skin sensitizatio	n			
Canada - Alberta OELs: Irri	tant			
Calcium Carbonate (CAS	S 471-34-1)		Irritant	
Respiratory sensitization	Not a resp	iratory sensitizer.		
Skin sensitization	This produ	ct is not expected to	cause skin sensitiza	ation.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.			
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.			
ACGIH Carcinogens				
Acetone (CAS 67-64-1)			A4 Not classifiable a	as a human carcinogen.
Canada - Manitoba OELs: c	arcinogenic	ity		
Acetone (CAS 67-64-1)	Not classifiable as a human carcinogen.		0	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.			
pecific target organ toxicity - ingle exposure	Narcotic e	fects.		
Specific target organ toxicity - epeated exposure	Not classif	ied.		
Aspiration hazard	Not likely,	due to the form of the	e product.	
Chronic effects	Prolonged	inhalation may be ha	armful.	
urther information	Symptoms	may be delayed.		
2. Ecological information	n			
Ecotoxicity	Not expect	ed to be harmful to a	quatic organisms.	
Components		Species		Test Results
Acetone (CAS 67-64-1)		•		
Aquatic				
Crustacea	EC50	Water flea (Dap	hnia magna)	10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout,do (Oncorhynchus		4740 - 6330 mg/l, 96 hours
Calcium Carbonate (CAS 47	1-34-1)		• •	
Aquatic	- /			
Fish	LC50	Western mosau	itofish (Gambusia at	ffinis) > 56000 mg/l, 96 hours
Distillates Petroleum Hydrotro			,	
<b>Aquatic</b> Fish	LC50	Rainbow trout,do (Oncorhynchus		2.9 mg/l, 96 hours
	Not inhoro	ntly biodegradable.	- /	
Persistence and degradability				

### Partition coefficient n-octanol / water (log Kow)

Acetone	
Mobility in soil	Not available.
Other adverse effects	None known.

### 13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazardous waste code	Not regulated.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Avoid discharge into water courses or onto the ground.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

-0.24

# 14. Transport information

TDG	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not available.
Environmental hazards	No
Special precautions for user	Not available.
ΙΑΤΑ	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not available.
Environmental hazards	No.
Special precautions for user	Not available.
Other information	
Passenger and cargo	Allowed with restrictions.
aircraft	
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not available.
Environmental hazards	
Marine pollutant	No
EmS	Not available.
Special precautions for user	
Transport in bulk according to	Not available.
Annex II of MARPOL 73/78 and	
the IBC Code	



# 15. Regulatory information

ion nogulator y miormation	•	
Canadian regulations	This product has been classified in accordance with the hazard criteric contains all the information required by the CPR.	a of the CPR and the SDS
Controlled Drugs and Subs	tances Act	
Not regulated.		
Export Control List (CEPA 1	999, Schedule 3)	
Not listed.		
Greenhouse Gases		
Carbon Dioxide (CAS 12		
	Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)	
Acetone (CAS 67-64-1) Precursor Control Regulation	nne	
Acetone (CAS 67-64-1)	Class B	
International regulations	The product is classified and labelled in accordance with EC directive	s or respective national laws
international regulations	This Safety Data Sheet complies with the requirements of Regulation people under 18 years old are not allowed to work with this product a 94/33/EC on the protection of young people at work.	(EC) No 1907/2006. Young
Stockholm Convention		
Not applicable.		
Rotterdam Convention		
Not applicable.		
Kyoto protocol		
Carbon Dioxide (CAS 12- Montreal Protocol	4-38-9) Listed.	
Not applicable.		
Basel Convention		
Not applicable.		
International Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	
Canada	Domestic Substances List (DSL)	
Canada	Non-Domestic Substances List (NDSL)	
China	Inventory of Existing Chemical Substances in China (IECSC)	
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	
Europe	European List of Notified Chemical Substances (ELINCS)	
Japan	Inventory of Existing and New Chemical Substances (ENCS)	
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### 16. Other information Issue date 06-16-2016 **Revision date** 07-11-2017 Version # 03 **Further information** HMIS® is a registered trade and service mark of the NPCA. References ACGIH EPA: AQUIRE database NLM: Hazardous Substances Data Base US. IARC Monographs on Occupational Exposures to Chemical Agents Korea. Accidental Release Prevention Substances (Presidential Decree of Toxic Chemical Control Law, Executive Order No. 19203) Korea. Dangerous Substances Threshold Quantity (Presidential Decree of Dangerous Substances Safety Management Act No. 18406, Schedule 1) Korea. Harmful Substances Prohibited from Manufacturing (Presidential Decree on the Industrial Safety and Health Act (No. 13053), Article 29) Korea. Harmful Substances Requiring Permission for Manufacture or Use (Presidential Decree on the Industrial Safety and Health Act (No. 13053), Article 30) Korea. Non-Toxic Chemicals List (National Institute of Environment Research (NIER) Public Notice No. 1997-10, as amended) Korea. Observational Chemicals (Ministerial Decree of TCCL Article 6) Korea. OELs. Regulation for Permitted Concentration of Hazardous Substances (Ministry of Labor (MOL) Public Notice No. 1986-45, as amended) Korea. Prohibited Chemical Substances (TCCL Article 11) Korea. Regulated volatile organic compounds (VOCs) (MOE Notice No. 2001-36, March 8, 2001, as amended) Korea. Restricted Chemical Substances (TCCL Article 11) Korea. Toxic Chemical Control Law (TCCL), Existing Chemicals Inventory (KECI) Korea. Toxic Chemical Control Law (TCCL), pre-1997 List Korea. Toxic Chemicals (TCCL Article 10) Korea. Toxic Release Inventory (TRI) Chemicals (TCCL Article 14) Taiwan. Dangerous Materials (Rules on Hazard Communication of Dangerous Materials and Toxic Materials) Taiwan. Industrial Precursor Chemicals (Categories and Regulations Governing Inspection and Declaration of Industrial Precursor Chemicals, MOEA Decree No. 87, as amended) Taiwan. OELs. (Standards on Workplace Atmosphere of Dangerous and Hazardous Materials) Taiwan. Toxic Chemical Substances (TCS) (List of Toxic Chemical Substances announced by the Environmental Protection Administration) Taiwan. Toxic Materials (Rules on Hazard Communication of Dangerous Materials and Toxic Materials) HSDB® - Hazardous Substances Data Bank IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices Japan Society for Occupational Health, Recommendation of Occupational Exposure Limits GOST 30333-2007 - Chemical production safety passport. General requirements JIS Z 7252:2009 Classification of chemicals based on "Globally Harmonized System of Classification and Labelling of Chemicals (GHS)" JIS Z 7253:2012 Hazard communication of chemicals based on GHS - Labelling and Safety Data Sheet (SDS) Japan Chemical Industry Association (JCIA) GHS Guideline, June 2012 This safety data sheet was prepared in accordance with JIS Z 7253:2012. Additional information is Disclaimer given in the Material Safety Data Sheet. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. **Revision information** Hazard(s) identification: Hazard statement Hazard(s) identification: Prevention Hazard(s) identification: Response Hazard(s) identification: Storage Composition / Information on Ingredients: Disclosure Overrides Regulatory Information: Risk Phrases - Labeling GHS: Classification