



Revision Number: 003.0

Issue date: 07/24/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE SF 7625 RUST TREATMENT known as Loctite(R) Extend(R) Rust Trea	IDH number:	234928
Product type:	Rust converter	Item number:	30539
Restriction of Use:	None identified	Region:	Canada
Company address:	Henkel Canada Corporation 2515 Meadowpine Boulevard Mississauga, Ontario L5N 6C3	Contact information:	Telephone: (905) 814-6511 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CONTENTS UNDER PRESSURE.
EXTREMELY FLAMMABLE AEROSOL.
HARMFUL IF SWALLOWED OR IF INHALED.
CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL	1
ACUTE TOXICITY ORAL	4
ACUTE TOXICITY INHALATION	4
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

PICTOGRAM(S)



Precautionary Statements

Prevention: Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust or fumes. Avoid breathing mist or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area.

Response: Wear protective gloves, clothing, eye and face protection.
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Wash contaminated clothing before reuse.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from
IDH number: 234928 Product name: LOCTITE SF 7625 RUST TREATMENT known as Loctite(R) Extend(R) Rust Trea

Disposal: sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
2-Butoxyethanol	111-76-2	30 - 40
Acetone	67-64-1	30 - 40
Formic acid	64-18-6	5 - 10

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Seek medical advice.

Skin contact: Remove contaminated clothing and footwear. Wash with soap and water. If symptoms develop and persist, get medical attention. Wash clothing before reuse.

Eye contact: Immediately flush eyes with water for at least 15 minutes, while holding eyelids open. Seek medical attention at once.

Ingestion: Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Dry chemical. foam

Special firefighting procedures: Use water spray to keep fire exposed containers cool and disperse vapors. Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Unusual fire or explosion hazards: Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.

Hazardous combustion products: Oxides of carbon. Hydrocarbons.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow material to contaminate ground water system. Do not let product enter drains. Absorb spill with inert material. Shovel material into appropriate container for disposal.

Clean-up methods: Absorb the spilled material with an inert absorbent (nonflammable) material.

7. HANDLING AND STORAGE

Handling: Avoid breathing mists or aerosols of this product. Keep away from sources of ignition - no smoking. Avoid contact with eyes, skin and clothing.

Storage: Store in a cool, dry area. Keep containers closed when not in use.

Shelf Life Statement: Not available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
2-Butoxyethanol	20 ppm TWA	50 ppm (240 mg/m ³) PEL (SKIN)	None	None
Acetone	250 ppm TWA 500 ppm STEL	1,000 ppm (2,400 mg/m ³) PEL	None	None
Formic acid	10 ppm STEL 5 ppm TWA	5 ppm (9 mg/m ³) PEL	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Aerosol, Liquid
Color:	Translucent
Odor:	Acetone
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	Not available.
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Specific gravity:	1.0000
Vapor density:	Not available.
Flash point:	< -17.7 °C (< 0.14 °F) ; This product exhibits no flashback when tested for flame extension.
Flammable/Explosive limits - lower:	1.1 %
Flammable/Explosive limits - upper:	57 %
Autoignition temperature:	Not available.
Flammability:	Extremely flammable aerosol.
Evaporation rate:	Not available.
Solubility in water:	Not available.
Partition coefficient (n-octanol/water):	Not available.
VOC content:	50.4 %
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Irritating organic vapours. Oxides of carbon.
Incompatible materials:	Acids and bases. Oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, spark and flame.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	Vapours may cause drowsiness and dizziness.
Skin contact:	Corrosive to the skin. Contact with the skin or mucous membranes may cause severe irritation and burns.
Eye contact:	Causes serious eye damage.
Ingestion:	Harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
2-Butoxyethanol	Oral LD50 (Rat) = 560 mg/kg Oral LD50 (Mouse) = 1.2 g/kg Oral LD50 (Rabbit) = 0.32 g/kg Oral LD50 (Rat) = 1.48 g/kg Oral LD50 (Mouse) = 1,519 mg/kg Dermal LD50 (Rabbit) = 400 mg/kg Inhalation LC50 (Rat, 4 h) = 486 ppm Inhalation LC50 (Rat, 4 h) = 450 ppm	Blood, Central nervous system, Irritant, Kidney, Liver
Acetone	Oral LD50 (Mouse) = 5.2 g/kg Oral LD50 (Mouse) = 3,000 mg/kg Oral LD50 (Rabbit) = 5,340 mg/kg Oral LD50 (Rat) = 5,800 mg/kg Oral LD50 (Rat) = 9,800 mg/kg Dermal LD50 (Rabbit) = 20,000 mg/kg Inhalation LC50 (Rat, 4 h) = 76 mg/l	Central nervous system, Irritant
Formic acid	Oral LD50 (Mouse) = 700 mg/kg Oral LD50 (Rat) = 730 mg/kg Inhalation LC50 (Rat, 4 h) = 7.4 mg/l	Central nervous system, Corrosive, Irritant, Kidney, Metabolic

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
2-Butoxyethanol	No	No	No
Acetone	No	No	No
Formic acid	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Recommended method of disposal: Not available.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name: AEROSOLS
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, flammable
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: AEROSOLS
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None
Additional information: IMDG-Code: Segregation group 1- Acids

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Cara R. Rivera, Regulatory Affairs Specialist

Issue date: 07/24/2017

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.