

LOCTITE 435 RUBBER TOUGH. INST

ADH known as LOCTITE® 435™

INSTANT ADHESIVE

Adhesive

Revision Number: 002.1



1. PRODUCT AND COMPANY IDENTIFICATION

IDH number:

Product name:

Product use:

Company address: Henkel Corporation 2515 Meadowpine Boulevard Mississauga. Ontario L5N 6C3 Item number:40994Region:CanadaContact information:Telephone:905.814.6511MEDICAL EMERGENCY Phone:Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone:CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet:www.henkelna.com

840057

2. HAZARDS IDENTIFICATION

	EMERGENCY OVERVIEW
Color: (Liquid WHMIS hazard class: B.3, D.2.B Clear, Colorless, Straw Sharp, Irritating
WARNING:	COMBUSTIBLE LIQUID AND VAPOR. BONDS SKIN IN SECONDS. MAY CAUSE EYE AND RESPIRATORY TRACT IRRITATION.
Relevant routes of exposure	Skin, Inhalation, Eyes
Potential Health Effects	
Inhalation:	Exposure to vapors above the established exposure limit results in respiratory irritation, which may lead to difficulty in breathing and tightness in the chest.
Skin contact:	Bonds skin in seconds. May cause skin irritation. Cyanoacrylates have been reported to cause allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare Cyanoacrylates generate heat on solidification. In rare circumstances a large drop will burn the skin. Cured adhesive does not present a health hazard even if bonded to the skin.
Eye contact: Ingestion:	Irritating to eyes. Causes excessive tearing. Eyelids may bond. Not expected to be harmful by ingestion. Rapidly polymerizes (solidifies) and bonds in mouth. It is almost impossible to swallow.
Existing conditions aggrava exposure:	ted by Eye, skin, and respiratory disorders.

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Ethyl 2-cyanoacrylate	7085-85-0	60 - 100
Thickener	Unknown	5 - 10

4. FIRST AID MEASURES

Inhalation:

Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.

IDH number: 840057

Product name: LOCTITE 435 RUBBER TOUGH. INST ADH known as LOCTITE® 435™ INSTANT ADHESIVE

Skin contact:	Do not pull bonded skin apart. Soak in warm soapy water. Gently peel apart using a blunt instrument. If skin is burned due to the rapid generation of heat by a large drop, seek medical attention. If lips are bonded, apply warm water to the lips and encourage wetting and pressure from saliva in mouth. Peel or roll lips apart. Do not pull lips apart with direct opposing force.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. Get medical attention. If eyelids are bonded closed, release eyelashes with warm water by covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Medical attention should be sought in case solid particles of polymerized cyanoacrylate trapped behind the eyelid caused abrasive damage.
Ingestion:	Ensure breathing passages are not obstructed. The product will polymerize rapidly and bond to the mouth making it almost impossible to swallow. Saliva will separate any solidified product in several hours. Prevent the patient from swallowing any separated mass.
Notes to physician:	Surgery is not necessary to separate accidentally bonded tissues. Experience has shown that bonded tissues are best treated by passive, non-surgical first aid. If rapid curing has caused thermal burns they should be treated symptomatically after adhesive is removed.

5. FIF	RE FIGHTING MEASURES	
Flash point:	80 - 93 °C (176°F - 199.4 °F) Tagliabue closed cup	
Autoignition temperature:	485 °C (905°F)	
Flammable/Explosive limits - lower:	Not available.	
Flammable/Explosive limits - upper:	Not available.	
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.	
Special firefighting procedures:	Wear a self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode.	
Unusual fire or explosion hazards:	Not available.	
Hazardous combustion products:	Trace amounts of toxic and/or irritating fumes may be released and the use of breathing apparatus is recommended.	
Sensitivity to Mechanical Impact:	Not available.	
Sensitivity to static discharge:	Not available.	
6. ACCIDENTAL RELEASE MEASURES		

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Ventilated area. Do not allow product to enter sewer or waterways.
Clean-up methods:	Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal burns.

Storage:

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

Shelf Life Statement: Not available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Ethyl 2-cyanoacrylate	0.2 ppm TWA	None	None	None
Thickener	None	None	None	None
Engineering controls:			tilation if general vent	
Respiratory protection:	controlled by w cartridge can b be monitored fu filter will becom	entilation a NIOSH ap e used. When such a requently as the cyan ne blocked. For that r	cyanoacrylate vapors proved respirator with a respirator is used ca oacrylate vapor will po eason we strongly rec respirator will not be r	an organic vapor rtridge function must olymerize and the commend that
Eye/face protection:			h side shields. Full fac or spraying of produc	
Skin protection:	Use nitrile glov PVC, nylon or		essary to prevent con	tact. Do not use

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Clear, Colorless, Straw
Odor:	Sharp, Irritating
Odor threshold:	Not available.
pH:	Not applicable
Vapor pressure:	< 0.2 mm hg
Boiling point/range:	> 149 °C (> 300.2 °F)
Melting point/ range:	Not determined
Specific gravity:	1.1
Vapor density:	3 Approximately
Flash point:	80 - 93 °C (176°F - 199.4 °F) Tagliabue closed cup
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	485 °C (905°F)
Evaporation rate:	Not available.
Solubility in water:	Polymerises in presence of water.
Partition coefficient (n-octanol/water):	Not available.
VOC content:	< 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated)

10. STABILITY AND REACTIVITY		
Stability:	Stable under recommended storage conditions.	
Hazardous reactions:	Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.	
Hazardous decomposition products:	Not available.	
Incompatible materials:	Water, Amines, Alkalis, Alcohols.	
Conditions to avoid:	Spontaneous polymerization.	
11. TOXIC	OLOGICAL INFORMATION	
Acute oral product toxicity:	LD50 (rat) > 5,000 mg/kg (Estimated)	
Acute dermal product toxicity:	LD50 (rabbit) > 2,000 mg/kg (Estimated)	

Toxicologically synergistic products: Not available.

Refer to the following for Irritancy of Product, Sensitization to Product, Carcinogenicity, Reproductive Toxicity, Teratogenicity, and Mutagenicity.

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)	ACGIH Carcinogen
Ethyl 2-cyanoacrylate	No	No	No	No
Thickener	No	No	No	No

Hazardous components	LD50s and LC50s	Health Effects/Target Organs
Ethyl 2-cyanoacrylate	None	Irritant, Allergen, Respiratory
Thickener	None	No Data

12. ECOLOGICAL INFORMATION

Ecological information:

Γ

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

Canada Transportation of Dangerous Goods - Ground

Proper shipping name: Hazard class or division: Identification number: Packing group: Not regulated None None None

International Air Transportation (ICAO/IATA)

Proper shipping name: Hazard class or division: Identification number: Packing group: Exceptions: Aviation regulated liquid, n.o.s. (Cyanoacrylate ester) 9 UN 3334 III Not more than 500 ml (each inner package) - Unrestricted

Water Transportation (IMO/IMDG) Proper shipping name: Hazard class or division: Identification number: Packing group:	Not regulated None None None
	15. REGULATORY INFORMATION
Canada Regulatory Information	
CEPA DSL/NDSL Status:	Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.
United States Regulatory Information	
TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: Reviewed MSDS. Reissued with new date.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation (CPR), and the MSDS contains all the information required by the CPR.

Prepared by: Catherine Bimler, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.