

Revision Number: 010.1 Issue date: 07/19/2017

1. PRODUCT AND COMPANY IDENTIFICATION

LOCTITE SF 790 GASKET REMOVER IDH number: Product name: 135544

known as LOCTITE® Chisel® Paint

Strippe

Product type: Cleaner Item number: 79040 Restriction of Use: None identified Region: Canada Contact information:

Company address:

Henkel Canada Corporation 2515 Meadowpine Boulevard

Mississauga, Ontario L5N 6C3

Telephone: (905) 814-6511 MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CONTENTS UNDER PRESSURE.

EXTREMELY FLAMMABLE AEROSOL.

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

CAUSES SKIN IRRITATION.

CAUSES SERIOUS EYE IRRITATION.

MAY CAUSE DROWSINESS OR DIZZINESS.

SUSPECTED OF CAUSING CANCER. CAUSES DAMAGE TO ORGANS.

MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR

REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL.	1
SKIN IRRITATION	2
EYE IRRITATION	2A
CARCINOGENICITY	2
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2
ASPIRATION HAZARD	1





Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been

> read and understood. Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

IDH number: 135544 Product name: LOCTITE SF 790 GASKET REMOVER known as LOCTITE® Chisel® Paint Strippe Do not breathe mist or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective

gloves, clothing, eye and face protection.

Response: IF SWALLOWED: Immediately call a physician or poison control center. IF ON SKIN: Wash

with plenty of water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed: Call a poison center or physician. Do NOT induce vomiting. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take

off contaminated clothing.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

2 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Methylene chloride	75-09-2	70 - 80
Propane/Isobutane	68476-86-8	20 - 30
Methanol	67-56-1	5 - 10

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). If

symptoms develop and persist, get medical attention.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Seek

medical advice.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious

person. If vomiting occurs, prevent aspiration by keeping the patient's head

below the knees. Call a physician immediately.

Symptoms: See Section 11.

IDH number: 135544

5. FIRE FIGHTING MEASURES

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Firefighters should wear self-contained breathing apparatus. Water may be

ineffective, but may be used to cool exposed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme

heat. If water is used, fog nozzles are preferable.

Unusual fire or explosion hazards: Vapours may accumulate in low or confined areas, travel considerable

distance to source of ignition, and flash back. Closed containers may rupture

(due to build up of pressure) when exposed to extreme heat.

Hazardous combustion products:

Irritating organic vapours. Phosgene. Hydrogen chloride. Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:Do not allow to enter the ground / soil.

Clean-up methods: Remove all sources of ignition. Spilled liquid is combustible and can be ignited

by heat, flames, sparks, or other sources of ignition. Store in a closed container until ready for disposal. Soak up with inert absorbent. Scrape up spilled material and place in a closed container for disposal. For small spills

wipe up with paper towel and place in container for disposal.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Avoid breathing mists or aerosols of this product.

Storage: For safe storage, store between 0 °C (32°F) and 32 °C (89.6 °F)

Store in a cool, dry, well-ventilated area. Store in original container until ready

to use.

Shelf Life Statement: Not available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Methylene chloride	50 ppm TWA	12.5 ppm OSHA_ACT 25 ppm TWA 125 ppm STEL	None	None
Propane/Isobutane	None	None	None	None
Methanol	200 ppm TWA (SKIN) 250 ppm STEL	200 ppm (260 mg/m3) PEL	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s). Use only in well-ventilated areas.

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. Silver Shield gloves. Viton gloves.

Polyvinyl alcohol gloves. 4H gloves. EVAL-Laminate gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:Aerosol, LiquidColor:Gray, to, Off whiteOdor:Sharp, SolventOdor threshold:Not available.

IDH number: 135544 Product name: LOCTITE SF 790 GASKET REMOVER known as LOCTITE® Chisel® Paint Strippe
Page 3 of 6

pH: Not available.
Vapor pressure: Not available.
Boiling point/range: Not available.
Melting point/ range: Not available.
Specific gravity: 0.789

Vapor density:Not available.Flash point:< 5 °C (< 41°F)</th>Flammable/Explosive limits - lower:Not available.Flammable/Explosive limits - upper:Not available.Autoignition temperature:Not available.

Flammability: Extremely flammable aerosol.

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

Viscosity:

Decomposition temperature:

Not available.

Not available.

Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 135544

Hydrogen chloride. Oxides of carbon. Irritating organic vapours. Phosgene.

Incompatible materials: Acids and bases. Oxidizing agents. Sodium. Potassium.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, spark and flame.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: Inhalation of vapor or aerosol may cause severe irritation to nose, throat and lungs. Excessive

inhalation of this material causes headache, dizziness, nausea and incoordination.

Skin contact: Causes skin irritation. May cause irritation due to defatting of the skin.

Eye contact: Causes serious eye irritation.

Ingestion: Aspirated material can enter lungs and cause damage. May cause dizziness, incoordination,

headache, nausea, and vomiting.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Methylene chloride	Oral LD50 (Rat) = 1,600 mg/kg Oral LD50 (Rat) = 3,000 mg/kg	Blood, Cardiac, Central nervous system, Corrosive, Irritant, Kidney, Liver, Some evidence of carcinogenicity
Propane/Isobutane	None	No Records
Methanol	Oral LD50 (Rat) = 5,628 mg/kg Oral LD50 (Mouse) = 7,300 mg/kg Oral LD50 (Rabbit) = 14.4 g/kg Dermal LD50 (Rabbit) = 15,800 mg/kg Inhalation LC50 (Rat, 4 h) = 64000 ppm	Eyes, Irritant, Metabolic, Nervous System

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Methylene chloride	Reasonably Anticipated to be a Human Carcinogen.	Group 2A	Yes
Propane/Isobutane	No	No	No
Methanol	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:

AEROSOLS
2.1 (6.1)
UN 1950
None

International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, flammable, containing substances in Division 6.1, Packing Group III

Hazard class or division: 2.1 (6.1)
Identification number: UN 1950
Packing group: None

Water Transportation (IMO/IMDG)

IDH number: 135544

Proper shipping name: AEROSOLS (Methylene chloride)

Hazard class or division: 2.1 (6.1)
Identification number: UN 1950
Packing group: None

15. REGULATORY INFORMATION

Canada Regulatory Information

IDH number: 135544

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Cara R. Rivera, Regulatory Affairs Specialist

Issue date: 07/19/2017

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.