Safety Data Sheet



Revision Number: 005.0

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

Product type: Epoxy Restriction of Use: None in Company address: Henkel Canada Corporation 2515 Meadowpine Boulevard Mississauga, Ontario L5N 6C3

LOCTITE EA 3472 STEEL LIQ known as Loctite(R) Fixmtr(R) Steel Liq Epoxy Hardener None identified

IDH number:

702245

Item number:97483_239000Region:CanadaContact information:Telephone:905) 814-6511MEDICAL EMERGENCY Phone:Poison Control Center1-877-671-4608 (toll free) or1-303-592-1711TRANSPORT EMERGENCY Phone:CHEMTREC1-800-424-9300 (toll free) or1-703-527-3887Internet:www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW			
DANGER:	HARMFUL IF SWALLOWED OR IN CONTACT WITH SKIN.		
	CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.		
	MAY CAUSE AN ALLERGIC SKIN REACTION.		
	MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING		
	DIFFICULTIES IF INHALED.		

HAZARD CLASS	HAZARD CATEGORY
ACUTE TOXICITY ORAL	4
ACUTE TOXICITY DERMAL	4
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1



Precautionary Statements

Prevention:

Response:

Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection. In case of inadequate ventilation wear respiratory protection. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF SWALLOWED: Rinse mouth. Do

NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If experiencing respiratory symptoms: Call a poison center or physician. Wash contaminated clothing before reuse.

Storage: Disposal: IDH number: 702245

Dispose of contents and/or container according to Federal, State/Provincial and local Product name: LOCTITE EA 3472 STEEL LIQ known as Loctite(R) Fixmtr(R) Steel Liq

governmental regulations.

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*	
Triethylenetetramine	112-24-3	30 - 40	
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer	68082-29-1	30 - 40	
N-Aminoethylpiperazine	140-31-8	10 - 20	
Nonylphenol	25154-52-3	5 - 10	
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	68953-36-6	1 - 5	
Glycerylpoly(oxypropylene)triamine	64852-22-8	1 - 5	
Diethylenetriamine	111-40-0	0.1 - 1	
4,4'-Isopropylidenediphenol	80-05-7	0.1 - 1	
Tetraethylene pentamine	112-57-2	0.1 - 1	

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4	. FIRST AID MEASURES
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
Skin contact:	Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). Get medical attention. Wash clothin before reuse. Thoroughly clean shoes before reuse.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.
5. F	FIRE FIGHTING MEASURES
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such a turn-out gear.
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen. Ammonia. Aldehydes. Acids. Phenolic Toxic fumes. Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	
----------------------------	--

Do not allow product to enter sewer or waterways.

Clean-up methods:

Ensure adequate ventilation. Wear appropriate personal protective equipment. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal.

7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not taste or swallow. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Storage:

Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Keep away from heat, spark and flame.

Shelf Life Statement: Not available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Triethylenetetramine	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer	None	None	None	None
N-Aminoethylpiperazine	None	None	None	None
Nonylphenol	None	None	None	None
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	None	None	None	None
Glycerylpoly(oxypropylene)triamine	None	None	None	None
Diethylenetriamine	(SKIN) 1 ppm TWA	None	None	None
4,4'-Isopropylidenediphenol	None	None	None	None
Tetraethylene pentamine	None	None	(SKIN) Aerosol. 1 ppm (5 mg/m3) TWA Aerosol. (Skin sensitizer)	None

Engineering controls:

Respiratory protection:

Eye/face protection:

Skin protection:

Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Liquid

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity:

Blue Ammoniacal Not available. Not available. Not available. 137 - 293 °C (278.6 - 559.4 °F) Not available. 0.99

Product name: LOCTITE EA 3472 STEEL LIQ known as Loctite(R) Fixmtr(R) Steel Liq Page 3 of 7

Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Flammability: Evaporation rate:	Not available. > 93 °C (> 199.4 °F) Not available. Not available. Not available. Not available. Not applicable Not available.
Flammability:	Not applicable
	11
Solubility in water:	Soluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	< 1.0 %; < 10 g/l (value for resin and hardener together) (estimated)
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.		
Hazardous reactions:	None under normal processing.		
Hazardous decomposition products:	Oxides of carbon. Ammonia. Aldehydes. Acids. Phenolics. Toxic fumes. Irritating vapors.		
Incompatible materials:	Strong oxidizing agents. Strong Lewis acids. Strong mineral acids. Strong bases. Aldehydes. Ketones. Acrylates. Organic halides.		
Reactivity:	Not available.		
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials.		
	11. TOXICOLOGICAL INFORMATION		
Polovant routes of expective	Skin Inholation Even Indeption		

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	May cause allergic respiratory reaction. Mists, vapors or liquid may cause severe irritation or burns.
Skin contact:	Causes skin burns. May cause allergic skin reaction. Harmful in contact with skin.
Eye contact:	Causes eye burns. Causes serious eye damage.
Ingestion:	If ingested, severe burns of the mouth and throat may occur, as well as perforation of the esophagus and the stomach. Harmful if swallowed. May cause an aspiration hazard if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Triethylenetetramine	None	Allergen, Corrosive, Developmental, Irritant, Mutagen
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer	None	No Records
N-Aminoethylpiperazine	None	Irritant, Corrosive, Allergen
Nonylphenol	Oral LD50 (Rat) = 1,600 mg/kg Dermal LD50 (Rabbit) = 2,140 mg/kg	Allergen, Corrosive, Irritant, Kidney
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	None	No Records
Glycerylpoly(oxypropylene)triamine	None	No Records
Diethylenetriamine	Oral LD50 (Rat) Approximate 1,140 mg/kg Oral LD50 (Rat) = 1,080 mg/kg Oral LD50 (Rat) = 2.33 g/kg	Allergen, Irritant, Eyes
4,4'-Isopropylidenediphenol	Oral LD50 (Rat) = 4,100 mg/kg Oral LD50 (Rat) = 3,300 mg/kg Oral LD50 (Mouse) = 5,280 mg/kg Oral LD50 (Mouse) = 2,500 mg/kg Oral LD50 (Mouse) = 4,100 mg/kg	Allergen, Blood, Irritant, Kidney, Reproductive, Spleen
Tetraethylene pentamine	Oral LD50 (Rat) = 3.99 g/kg Oral LD50 (Rat) = 2.1 g/kg Dermal LD50 (Rabbit) = 0.66 g/kg	Irritant, Mutagen, Allergen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Triethylenetetramine	No	No	No
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer	No	No	No
N-Aminoethylpiperazine	No	No	No
Nonylphenol	No	No	No
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	No	No	No
Glycerylpoly(oxypropylene)triamine	No	No	No
Diethylenetriamine	No	No	No
4,4'-Isopropylidenediphenol	No	No	No
Tetraethylene pentamine	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration. Canada Transportation of Dangerous Goods - Ground AMINES, LIQUID, CORROSIVE, N.O.S. (Aminoethylpiperazine, Proper shipping name: Triethylenetetramine, Nonylphenol) Hazard class or division: 8 Identification number: UN 2735 Packing group: Ш International Air Transportation (ICAO/IATA) Proper shipping name: Amines, liquid, corrosive, n.o.s. (Aminoethylpiperazine, Triethylenetetramine, Nonylphenol) Hazard class or division: 8 Identification number: UN 2735 Packing group: Ш Water Transportation (IMO/IMDG) Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Aminoethylpiperazine, Triethylenetetramine, Nonylphenol) Hazard class or division: 8 Identification number: UN 2735 Packing group: Ш Marine pollutant: Nonylphenol 15. **REGULATORY INFORMATION**

Canada Regulatory Information

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Rebecca Coons, Regulatory Affairs Specialist

Issue date: 01/18/2017

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Safety Data Sheet



Revision Number: 005.0

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

Product type: Epoxy Restriction of Use: None in Company address: Henkel Canada Corporation 2515 Meadowpine Boulevard Mississauga, Ontario L5N 6C3

LOCTITE EA 3472 STEEL LIQ known as Loctite(R) Fix(R) Steel Liquid Epoxy resin None identified

IDH number:


702244

Item number:97483_10256000Region:CanadaContact information:Telephone:905) 814-6511MEDICAL EMERGENCY Phone:Poison Control Center1-877-671-4608 (toll free)or 1-303-592-1711TRANSPORT EMERGENCY Phone:CHEMTREC1-800-424-9300 (toll free)or 1-703-527-3887Internet:www.henkelna.com

2. HAZARDS IDENTIFICATION

	EMERGENCY OVERVIEW
WARNING:	CAUSES SKIN IRRITATION.
	MAY CAUSE AN ALLERGIC SKIN REACTION.
	CAUSES SERIOUS EYE IRRITATION.
	MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3



Precautionary Statements

Prevention:	Avoid breathing dust or fumes. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.
Response:	IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
Storage:	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

IDH number: 702244

Product name: LOCTITE EA 3472 STEEL LIQ known as Loctite(R) Fix(R) Steel Liquid

Page 1 of 5

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*	
Diiron trioxide	1309-37-1	30 - 60	
Epoxy resin	Proprietary	30 - 60	
Neopentyl glycol diglycidyl ether	17557-23-2	1 - 5	
Manganese	7439-96-5	0.1 - 1	
Substituted silane	Proprietary	0.1 - 1	

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention. Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. If symptoms develop and persist, get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
contaminated clothing and footwear. If symptoms develop and persist, get medical attention. Wash clothing before reuse. Thoroughly clean shoes before
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
See Section 11.
E FIGHTING MEASURES
Water spray (fog), foam, dry chemical or carbon dioxide.
Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA). In case of fire, keep containers cool with water spray. Caution should be exercised when using water or foam as frothing may occur.
Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Oxides of carbon. Acids. Phenolics. Toxic fumes. Aldehydes. Irritating organic fragments.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean- up. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Use only with adequate ventilation. Keep container closed.

Storage:

Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Store away from heat, sparks, flames, or other sources of ignition.

For information on product shelf life contact Henkel Canada Customer Service at 800-263-5043.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Diiron trioxide	5 mg/m3 TWA Respirable fraction.	10 mg/m3 PEL Fume.	None	None
Epoxy resin	None	None	None	None
Neopentyl glycol diglycidyl ether	None	None	None	None
Manganese	0.02 mg/m3 TWA (as Mn) Respirable fraction. 0.1 mg/m3 TWA	5 mg/m3 Ceiling (as Mn) Fume.	None	None
	(as Mn) Inhalable fraction.			
Substituted silane	None	None	None	None
Engineering controls:	Provide adequa exposure limits		lation to maintain work	ker exposure below
Respiratory protection:	Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.			
Eye/face protection:	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.			
Skin protection:		esistant, impermeable suit to prevent skin co	e clothing including glov ntact.	ves and either an

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste Color: Gray Odor: mild Odor threshold: Not available. Not available. pH: Vapor pressure: Not applicable Boiling point/range: Not applicable Melting point/ range: Not available. Specific gravity: 2.352 Vapor density: > 1 (Air = 1) Flash point: 204 °C (399.2 °F) Pensky Martens closed cup Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Flammability: Not applicable Evaporation rate: Less than butyl acetate. Solubility in water: Insoluble Partition coefficient (n-octanol/water): Not available. **VOC content:** < 1.0 %; < 10 g/l (value for resin and hardener together) (estimated)

Product name: LOCTITE EA 3472 STEEL LIQ known as Loctite(R) Fix(R) Steel Liquid Page 3 of 5

Viscosity:	Not available.
Decomposition temperature:	Not available.
	10. STABILITY AND REACTIVITY
Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Acids. Phenolics. Aldehydes. Toxic fumes. Irritating vapors.
Incompatible materials:	Strong oxidizing agents. Strong Lewis acids. Strong mineral acids. Strong bases. Amines. Mercaptans. Strong alkalis.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials.
	11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	Inhalation of vapors or mists of the product may be irritating to the respiratory system. Central nervous system effects.
Skin contact:	Causes skin irritation. May cause allergic skin reaction. May cause central nervous system effects.
Eye contact:	Causes serious eye irritation.
Ingestion:	May cause gastrointestinal tract irritation if swallowed. Ingestion of larger amounts may cause defects to the central nervous system (e.g. dizziness, headache).

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Diiron trioxide	None	Allergen, Cardiac, Central nervous system, Irritant, Kidney, Liver, Lung
Epoxy resin	None	Allergen, Irritant
Neopentyl glycol diglycidyl ether	None	Allergen, Blood, Bone Marrow, Immune system, Irritant, Reproductive
Manganese	None	Immune system, Irritant, Lung, Nervous System, Reproductive, Respiratory
Substituted silane	None	Allergen, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Diiron trioxide	No	No	No
Epoxy resin	No	No	No
Neopentyl glycol diglycidyl ether	No	No	No
Manganese	No	No	No
Substituted silane	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

	13. DISPOSAL CONSIDERATIONS				
Information provided is for unused product only.					
Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.					
	14. TRANSPORT INFORMATION				
The transport information provided i package/configuration.	n this section only applies to the material/formulation itself, and is not specific to any				
Canada Transportation of Dangerous Proper shipping name: Hazard class or division: Identification number: Packing group:	Not regulated None None None				
International Air Transportation (ICA Proper shipping name: Hazard class or division: Identification number: Packing group:	O/IATA) Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorhydrin resin) 9 UN 3082 III				
Water Transportation (IMO/IMDG) Proper shipping name: Hazard class or division: Identification number: Packing group: Marine pollutant:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A Epichlorhydrin resin) 9 UN 3082 III Bisphenol-A Epichlorhydrin resin				
	15. REGULATORY INFORMATION				
Canada Regulatory Information					
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.				
United States Regulatory Information					
TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.				

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Rebecca Coons, Regulatory Affairs Specialist

Issue date: 07/05/2016

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.